UNIFLEX SHELTERS MODELS AND SPECIFICATIONS

11 FOOT DISASTER RELIEF SHELTER TYPE II

Special Features: The Uniflex Disaster relief shelter Type II is flexible and integral no assembly required set-up involves the placement of interlocking metal support tubes. The fastest erecting Disaster relief shelter available. Period.

MODEL NUMBER	1106	1110	1114	1118
Roof & Sidewall Material	4MM white P/P	4MM white P/P	4MM white P/P	4MM white P/P
Floor Material	4MM non-skid P/P	4MM non-skid P/P	4MM non-skid P/P	4MM non-skid P/P
Endwall Material	Vintex Fabric	Vintex Fabric	Vintex Fabric	Vintex Fabric
Erection Time	45 seconds	45 seconds	45 seconds	45 seconds
Temporary Use	Yes	Yes	Yes	Yes
Permanent Use	1-5 years	1-5 years	1-5 years	1-5 years
Interior Walls	Optional	Optional	Optional	Optional
Packed Size	85” x 85” x 12”	85” x 85” x 16”	85” x 85” x 20”	85” x 85” x 24”
Size	50 Cubic Feet	66 Cubic Feet	84 Cubic Feet	100 Cubic Feet
Size Erected	11’ x 6’ x 9’4”	11’ x 10’ x 9’4”	11’ x 14’ x 9’4”	11’ x 18’ x 9’4”
Product Weight	71 lbs	114 lbs	157 lbs	200 lbs
Packed Weight	178 lbs	221 lbs	264 lbs	307 lbs
Snowload	5-10 lbs/sq.ft	5-10 lbs/sq.ft	5-10 lbs/sq.ft	5-10 lbs/sq.ft

11 FOOT DISASTER RELIEF SHELTER TYPE II

MODEL NUMBER	1106	1110	1114	1118
Maximum Accumulation	Approx.6lbs/sq.ft Or up to 12” depth	Approx.6lbs/sq.ft Or up to 12” depth	Approx.6lbs/sq.ft Or up to 12” depth	Approx.6lbs/sq.ft Or up to 12” depth
Insulation Factor Endwalls	1 - 4	1 - 4	1 - 4	1 - 4
Maximum Wind Speed	72mph	72mph	72mph	72mph

Product Accessories:

- Propane Heaters
- Thermal Boot
- Extra Windows and Doors

Option for Uniflex Disaster Relief Shelters

- Custom Colours
- Holographic imaging from supplied camera ready artwork
- Lighting kits

Production Capacity: With 6 weeks notification Pine Valley Packaging Limited can produce up to 250 Uniflex shelter kits per week, dependant on size.