

UNIFLEX SHELTERS MODELS AND SPECIFICATIONS

10 FOOT EASY GROW GREENHOUSE

Special Features: The Uniflex greenhouse is flexible and integral, no assembly required. Setup involves the placement of interlocking metal support tubes once the greenhouse has been erected. The fastest erecting greenhouse available. Period.

<u>MODEL NUMBER</u>	<u>1006</u>	<u>1010</u>	<u>1014</u>	<u>1018</u>
Roof & Sidewall Material	4MM Polycarbonate Polycarbonate	4MM Polycarbonate	4MM Polycarbonate	4MM
Floor Material Polycarbonate	4MM Polycarbonate	4MM Polycarbonate	4MM Polycarbonate	4MM
Endwall Material	Vintex Fabric	Vintex Fabric	Vintex Fabric	Vintex Fabric
Zippered Doorway	1 Standard	1 Standard	1 Standard	1 Standard
Zippered Window	2 Standard	2 Standard	2 Standard	2 Standard
Temporary Use	Yes	Yes	Yes	Yes
Permanent Use	5 – 10 years	5 – 10 years	5 – 10 years	5 – 10 years
Interior Walls	Optional	Optional	Optional	Optional
Packed Carton	75" x 75" x 12"	75" x 75" x 16"	75" x 75" x 20"	75" x 75" x 24"
Size	36' Cube	52' Cube	52' Cube	52' Cube
Size Erected	10' x 6' x 7'2"	10' x 10' x 7'2"	10' x 14' x 7'2"	10' x 18' x 7'2"

<u>MODEL NUMBER</u>	<u>1006</u>	<u>1010</u>	<u>1014</u>	<u>1018</u>
Product Weight	56 lbs	84 lbs	112 lbs	140 lbs
Packed Weight	159 lbs	187 lbs	215 lbs	243 lbs
Snowload	5-10 lbs/sq.ft	5-10 lbs/sq.ft	5-10 lbs/sq.ft	5-10 lbs/sq.ft
Maximum Accumulation 6lbs/sq.ft	Approx 6lbs/sq.ft Or 12" Depth	Approx 6lbs/sq.ft Or 12" Depth	Approx 6lbs/sq.ft Or 12" Depth	Approx Or 12" Depth
Insulation Factor Roof / Sidewalls & Floor	1 – 4	1 – 4	1 – 4	1 – 4
Insulation Factor Endwalls	0	0	0	0
Maximum Wind Speed	80mph	80mph	80mph	80mph
Light Transmission	60%	60%	60%	60%

Accessory Items Available

- A) 2 x 12 wolvanized base frame
- B) Two speed 12" exhaust fan and thermostat
- C) Extra windows and doors
- D) Grow zone tables

Product Life Expectancy Note: Polycarbonate material has a 10 year manufacturer's guarantee.

Recommendations: - Line greenhouse floor with paving stone to provide stability.
- For uneven surfaces a 2 x 12 wolvanized perimeter wood frame is recommended.