

## UNIFLEX SHELTERS MODELS AND SPECIFICATIONS

### 10 FOOT EMERGENCY RESPONSE

**Special Features:**

The Uniflex greenhouse is flexible and integral, no assembly required, minimum setup can be shipped with shower stalls, basins and plumbing kits already built in. The fastest erecting shelter available. Period.

<b><u>MODEL NUMBER</u></b>	<b><u>1006</u></b>	<b><u>1010</u></b>	<b><u>1014</u></b>	<b><u>1018</u></b>
Roof & Sidewall	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene
Floor Material	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene
Endwall Material	Nylon	Nylon	Nylon	Nylon
Erection Time	30 Seconds	30 Seconds	30 Seconds	30 Seconds
Temporary Use	Yes	Yes	Yes	Yes
Permanent Use	No	No	No	No
Interior Walls	Optional	Optional	Optional	Optional
Packed Carton	75" x 75" x 12"	75" x 75" x 16"	75" x 75" x 20"	75" x 75" x 24"
Size	36 Cubic feet	52 Cubic feet	65 Cubic feet	75 Cubic feet
Size Erected	10' x 6' x 7'2"	10' x 10' x 7'2"	10' x 14' x 7'2"	10' x 18' x 7'2"
Product Weight	56lbs	84lbs	112lbs	140lbs
Packed Weight	159 lbs	187 lbs	215 lbs	243 lbs

## **10 FOOT EMERGENCY RESPONSE SHELTER**

<b><u>MODEL NUMBER</u></b>	<b><u>1006</u></b>	<b><u>1010</u></b>	<b><u>1014</u></b>	<b><u>1018</u></b>
Snow load	5lbs/sq.ft.	5lbs/sq.ft.	5lbs/sq.ft.	5lbs/sq.ft.
Maximum Accumulation	Approx 3lbs/sq.ft Or 6" Depth	Approx 3lbs/sq.ft Or 6" Depth	Approx 3lbs/sq.ft Or 6" Depth	Approx 3lbs/sq.ft Or 6" Depth
Insulation Factor Roof / Sidewalls & Floor	1 – 4	1 – 4	1 – 4	1 – 4
Insulation Factor Endwalls	0	0	0	0
Maximum Wind Speed	72mph	72mph	72mph	72mph
Product Accessories:				
A) Heater				
B) Thermometer				
C) Shower Stalls				
D) Shower Basins				
E) Plumbing Kits				
F) Spray wands				