UNIFLEX SHELTERS MODELS AND SPECIFICATIONS

11 FOOT EMERGENCY RESPONSE

Special Features: The Uniflex greenhouse is flexible and integral, no assembly required, minimum setup can be shipped with shower stalls, basins and plumbing kits already built in. The fastest erecting shelter available. Period.

MODEL NUMBER	1106	1110	1114	1118
Roof & Sidewall	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene
Floor Material	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene	4MM Polypropylene
Endwall Material	Nylon	Nylon	Nylon	Nylon
Erection Time	30 Seconds	30 Seconds	30 Seconds	30 Seconds
Temporary Use	Yes	Yes	Yes	Yes
Permanent Use	No	No	No	No
Interior Walls	Optional	Optional	Optional	Optional
Packed Carton	85” x 85” x 12”	85” x 85” x 16”	85” x 85” x 20”	85” x 85” x 24”
Size	50 Cubic feet	66 Cubic feet	84 Cubic feet	100 Cubic feet
Size Erected	11’ x 6’ x 9’4”	11’ x 10’ x 9’4”	11’ x 14’ x 9’4”	11’ x 18’ x 9’4”
Product Weight	71lbs	114lbs	157lbs	200lbs
Packed Weight	178 lbs	221 lbs	264 lbs	307 lbs

11 FOOT EMERGENCY RESPONSE SHELTER

MODEL NUMBER	**1106**	**1110**	**1114**	**1018**
Snow load	5lbs/sq.ft.	5lbs/sq.ft.	5lbs/sq.ft.	5lbs/sq.ft.
Maximum Accumulation	Approx 3lbs/sq.ft Or 6” Depth	Approx 3lbs/sq.ft Or 6” Depth	Approx 3lbs/sq.ft Or 6” Depth	Approx 3lbs/sq.ft Or 6” Depth
Insulation Factor Roof / Sidewalls & Floor	1 – 4	1 – 4	1 – 4	1 – 4
Insulation Factor Endwalls	0	0	0	0
Maximum Wind Speed	72mph	72mph	72mph	72mph

Product Accessories:

A) Heater
B) Thermometer
C) Shower Stalls
D) Shower Basins
E) Plumbing Kits
F) Spray wands